

Brand – Nax Radiant


Nax Radiant Binder 300 Metallic Base

Product Description


Nax Radiant Base coat Binder is a premium quality binder in basecoat with best in class for aluminium orientation, flow and levelling.

Properties

- Appearance – Translucent
- Supply Viscosity @ 30° - 220 ± 20 seconds by B4 cup @ 30°C
- Non Volatile Material in percentage- 13 ± 2 %
- For well -stored products at around 70°F-95°F (20°C-35°C) without much temperature fluctuations, a shelf life of 1 year can be expected.

Mixing Ratio (When made Base coat with B/C Binder + Toner)


1 parts Nax Radiant Base coat
 80 – 120 % Nax Value thinner

Application (When made Base coat with B/C Binder + Toner)


Spray Viscosity – 16 – 19 Secs in B4 Cup at 30°C



Spray gun	Fluid tip set-up	Application Pressure
Gravity Feed	1.3–1.4 mm	40 to 45 psi at the spray gun air inlet for conventional guns For HVLP- 25-30 Psi For Compliant – 30-35 Psi



- Apply 2 single coats, allowing for a 5-10 minutes of flash off time.

FOR PROFESSIONAL USE ONLY

The Product is suitable strictly for professional use only. The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only.

NIPPON PAINT INDIA PVT LTD
 Plot No 229, Patparganj industrial Area
 New Delhi-110092
www.nipponpaint.com.in

Drying Time (When made Base coat with B/C Binder + Toner)

- Dust Free Dry -10 – 15 min - air drying at 30°C and 65% Relative Humidity
- Recoatable Dry- 25 – 35 Minutes 30°C and 65% Relative Humidity

Film Thickness & Material usage (When made Base coat with B/C Binder + Toner)

- Dry Film Thickness – 10-15 microns for 2 coats application at 30°C

Product Features

- Nax Radiant Internationally OEM approved brand at a competitive price with no compromise on performance

FOR PROFESSIONAL USE ONLY

The Product is suitable strictly for professional use only. The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only.

NIPPON PAINT INDIA PVT LTD
Plot No 229, Patparganj industrial Area
New Delhi-110092
www.nipponpaint.com.in